



product_datasheet_title

ENDURA Classic Beam Wall Down GU10

ENDURA® BEAM | GU10 socketed luminaires with classic shape and light outlet up and down



technical_data

ELECTRICAL DATA


Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

PHOTOMETRICAL DATA

Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0

DIMENSIONS & WEIGHT

Length	104.00 mm
Width	92.00 mm
Height	146.00 mm
Product weight	601.00 g



MATERIALS & COLORS

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Glass
Mercury content	0.0 mg

APPLICATION & MOUNTING

Type of connection	Terminal, 3-Pole (L, N, PE)
--------------------	-----------------------------

Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	no
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
With light source	No
Holder designation	GU10

EMERGENCY LIGHTING

Type of emergency light operation	Non-maintained
Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	-





CERTIFICATES & STANDARDS

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

ADDITIONAL PRODUCT DATA

Product remark	Maximum bulb wattage: 35 W
Number of illuminants	1

download_data

Documents and certificates		document_name
	User instruction	ENDURA CLASSIC
	Packaging insert	Legal insert I-Outdoor
	Declarations Of Conformity CE	
	Declarations Of Conformity UKCA	Fixed LUM without EMC

logistical_data

product_code	packaging_unit	dimensions	weight	volume
--------------	----------------	------------	--------	--------

product_code	packaging_unit	dimensions	weight	volume
4058075554535	Folding box 1	100 mm x 110 mm x 155 mm	653.00 g	1.71 dm ³
4058075554542	Shipping box 4	245 mm x 220 mm x 180 mm	2914.00 g	9.70 dm ³

logistical_data_text

disclaimer_title

disclaimer_text