



product_datasheet_title

LED Bulkhead 6W 4000K White

LED BULKHEAD | Wall and ceiling luminaires



technical_data

ELECTRICAL DATA


Nominal wattage	6.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	52.000 mA
Power factor λ	> 0.5
Protection class	II
Operating mode	Mains voltage

PHOTOMETRICAL DATA

Luminous flux	420 lm
Total luminous flux of contained light sources	600 lm
Luminous efficacy	76 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥ 80
Beam angle	120 °

DIMENSIONS & WEIGHT

Length	117.00 mm
Width	168.00 mm
Height	70.00 mm
Product weight	175.00 g



LED BULKHEAD 6W

MATERIALS & COLORS

Product color	White
---------------	-------

Housing color	White
Body material	Polycarbonate (PC)
Cover material	Acrylonitrile butadiene styrene (ABS)
Mercury content	0.0 mg

APPLICATION & MOUNTING

Ambient temperature range	-20...+40 °C
Type of connection	Screw terminal
Type of protection	IP54
Protection class IK (shock resistance)	IK06
Dimmable	no
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

LIFESPAN

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)



CERTIFICATES & STANDARDS



Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

ADDITIONAL PRODUCT DATA

Number of illuminants	empty
-----------------------	-------

download_data

Documents and certificates		document_name
	User instruction	LED BULKHEAD
	Packaging insert	Legal insert

Documents and certificates		document_name
	Declarations Of Conformity CE	LED BULKHEAD
	Declarations Of Conformity UKCA	Fixed LUM

logistical_data

product_code	packaging_unit	dimensions	weight	volume
4058075271586	Folding box 1	78 mm x 124 mm x 177 mm	202.00 g	1.71 dm ³
4058075271593	Shipping box 8	327 mm x 263 mm x 196 mm	1924.00 g	16.86 dm ³

logistical_data_text

disclaimer_title

disclaimer_text